



DRIPWAVE®

**1 3/8" GROUND, .019 GALVANIZED STEEL
WITH G90 COATING**

NEXT GENERATION INSULATION SYSTEMS

DRIPWAVE® WEEP/VENT SCREED

DESCRIPTION

DripWave® Weep/Vent Screed is fabricated from prime hot-dipped galvanized steel (minimum .019 thickness) and G90 coating conforming to the ASTM A653/A653M specification for coated steel. DripWave® Vent/Weep Screed was designed specifically for use in and as a component of the patented DripWave® Insulation System. DripWave® Vent/Weep Screed is available with a 1 3/8" ground for use in 1-coat stucco applications. DripWave® Vent/Weep Screed is approved for use in residential, multi-family residential, and commercial structures that are less than 6 stories in height.

PREPARATION

Ensure all substrates are clean, dry, and free from substances and protrusions that could adversely affect the weep/vent screed and compromise the system. Wall system must be properly designed and structurally sound. Planar irregularities must not exceed 1/4" over 10". Maximum allowable deflection of structural wall components is 1/360 of the span. Wood-based sheathing should be installed using corrosion-resistant fasteners per manufacturer's written specifications and in compliance with all applicable building codes.

INSTALLATION

Align DripWave® Weep/Vent Screed with sill plate and install a minimum of 4" above grade, 2" above finished grade, or as specified by local code. In vented insulation systems, the DripWave® Weep/Vent Screed must be installed at the bottom of the wall to allow water to drain from the wall system. In ventilated insulation systems, the DripWave® Weep/Vent Screed must be installed at the bottom of the wall to allow water to drain from the wall system and at the top of the wall to allow air to enter and escape from the wall system. See StyTek Installation guidelines for DripWave® Weep/Vent Screed specific installation details.

APPROVED FASTENERS

Fasteners must be galvanized and comply with industry standards and all applicable building codes. The following fasteners are recommended for installation of the DripWave® Vent/Weep Screed.

- Galvanized 5d x 1 1/4" or #11 x 1 1/4" Roofing Nails

PHYSICAL PROPERTIES

PROPERTIES		STANDARD
Galvanized Steel	.019"	ASTM A653/A653M
Coating: Hot Dipped Zinc	G90	ASTM A653/A653M
DIMENSIONS		
Nailing Flange	3 1/2"	
Ground	1 3/8"	
Return Key	1/4"	
Length	120"	

**DripWave® Weep/Vent Screed Meets or Exceeds
ASTM Standards**

March 2021



Page 1 of 2

stytek

www.stytek.com | 916.383.0500 | 6200 Sky Creek Drive, Sacramento, CA 95828

© 2021 StyTek LLC. All Rights Reserved. DripWave® is a Registered Trademark of StyTek LLC. Infringers will be prosecuted to the fullest extent of the law.

LIMITATIONS

Exposed surfaces of the DripWave® Weep/Vent Screed must be primed and painted to ensure long term performance and durability. Failing to do so could cause premature product degradation.

STORAGE & HANDLING

DripWave® Weep/Vent Screed are packaged in boxes of 20 pieces. Store boxes in a dry location protected from the weather. The boxes should be stored flat on the ground not more than 5 boxes high. DripWave® Weep/Vent Screed should remain in the boxes until installation. To avoid damage, do not place anything on top of the weep/vent screed boxes.

When loading DripWave® Weep/Vent Screeds onto a flatbed truck they must be protected on top during strapping to avoid damage. Use sheet metal corner guards underneath each strap. Do not allow weep/vent screeds to fall or be thrown from the truck, this may damage the weep/vent screeds.

DRIPWAVE® PLUS 10 YEAR SYSTEM WARRANTY



When the DripWave® Weep/Vent Screed is used in combination with DripWave® EPS panels or DripWave® Plus EPS panels and DripWave® Mesh Tape or DripWave® Panel Tape, and the DripWave® High Performance or DripWave® High Performance Plus Installation Guidelines, a 10 Year Parts & Labor warranty is provided. Consult StyTek LLC for additional information.

DRIPWAVE® MAX PLUS 20 YEAR SYSTEM WARRANTY



When the DripWave® Weep/Vent Screed is used in combination with DripWave® Plus EPS panels, DripWave® Panel Tape, and the DripWave® High Performance Max Plus Installation Guideline, a 20 Year Parts & Labor warranty is provided. Consult StyTek LLC for additional information.

LIMITED LIFETIME PRODUCT WARRANTY



StyTek LLC warrants that its DripWave® Weep/Vent Screed will perform as described in their product literature and applicable product data sheets for a period of 50 years from the date of purchase. This warranty only applies if the product is properly installed, maintained, and used for the purpose in which the manufacturer intended. Consult StyTek LLC for additional information.